

CS'E


Subnetting a class B address

Class B

16 bits	8 bits	8 bits
netid = 140.252	subnetid	hostid

Wireless & Multimedia Network Laboratory™

Wireless Multimedia



CS'E

Routing Principles

- ♦ A matching host address is always used before a matching network address: routing mechanism:
 - 1. Search for a matching host address.
 - 2. Search for a matching network address.
 - 3. Search for a default entry.

Wireless & Multimedia Network Laboratory™

Wireless Multimedia

CS'E

Simple Routing Table

- ♦ A example routing table:
- ♦ netstat options:
 - -r option: list the routing table
 - -n option: print IP address in numeric format

```

svr4 % netstat -rn
Routing tables
Destination      Gateway         Flags   Refcnt  Use    Interface
140.252.13.65    140.252.13.35  UGH     0        0     emd0
127.0.0.1        127.0.0.1      UH       1        0     lo0
default          140.252.13.33  UG       0        0     emd0
140.252.13.32    140.252.13.34  U        4       25043   emd0

```

Wireless & Multimedia Network Laboratory™

Wireless Multimedia

CS'E

Simple Routing Table

- ♦ (continued...)
- ♦ Flags:
 - U the route is up
 - G the route is gateway (router)
 - H the route is to a host
 - D the route was created by a redirect
 - M the route was modified by a redirect

```

svr4 % netstat -rn
Routing tables
Destination      Gateway         Flags   Refcnt  Use    Interface
140.252.13.65    140.252.13.35  UGH     0        0     emd0
✓ 127.0.0.1        127.0.0.1      UH       1        0     lo0
default          140.252.13.33  UG       0        0     emd0
140.252.13.32    140.252.13.34  U        4       25043   emd0

```

Wireless & Multimedia Network Laboratory™

Wireless Multimedia

CS'E

Simple Routing Table

- ♦ The G Flag:
 - not set for a direct route, else for indirect route
- ♦ A packet goes out a direct route:
 - both the IP address and the link-layer address specifying the destination
- ♦ A packet goes out a indirect route:
 - the IP address specifies the final destination but the link-layer address specifies the gateway(the next-hop router)
- ♦ The H Flag:
 - set for a host address, searched first by the routing principle

Wireless & Multimedia Network Laboratory™

Wireless Multimedia

Simple Routing Table

- ◆ The complexity of a routing table:
 - simplest: not connected to the network: only a single entry for the loopback interface
 - connected to a single LAN: only able to access hosts on that LAN: two entries, one for loopback, one for LAN
 - other networks are reachable through a single router: normally handled with a default entry pointing to that router
 - host-specific or network-specific routes are added

Simple Routing Table

- ◆ illustration by an example (the host svr4):
 - the destination is the host sun, 140.252.13.33 ... not match any host entry ... matches 140.252.13.32 (the network IDs and subnet IDs match) ... so emd0 interface is used
 - the destination is the host slip, 140.252.13.65 ... matches the host entry ... and then indirect route
 - the destination is the host aw.com (192.207.117.2) ... not match any host entry ... not match any network entry ... searched for a default route ... then indirect route to the gateway 140.252.13.33 using the interface emd0

Initializing a Routing Table

- ◆ an interface initialized, then automatically create a direct route in the routing table
- ◆ use route command to assign a route explicitly
 - Route add default sun 1
- ◆ run a routing daemon or use the newer router discovery protocol

A More Complex Routing Table

```
sun % netstat -rn
Routing tables
Destination Gateway      Flags  Refcnt Use  Interface
140.252.13.65 140.252.13.33 UGH    0      171  le0
127.0.0.1     127.0.0.1     UH     1       766  le0
140.252.1.183 140.252.1.29  UH     0       0     sl0
default       140.252.1.183 UH     1      2955  sl0
140.252.13.32 140.252.13.33 U       8     99551  le0
```

```
sun % ifconfig sl0
sl0: flags=105<UP,POINTOPOINT,RUNNING>
inet 140.252.1.29 --> 140.252.1.183 netmask ffffffff
```

No Route to Destination

- ◆ If there is NO default route:
 - for the IP datagram was generated on the host: an error the application that sent the datagram: "host unreachable" or "network unreachable"
 - for the IP datagram is being forwarded: an ICMP host unreachable is sent back to original sender

ICMP Host and Network Unreachable Errors

- ◆ The ICMP "host unreachable" error message is sent by a router when it receives an IP datagram that it cannot deliver or forward:

```
svr4 % ping gemini
ICMP Host Unreachable from gateway sun (140.252.13.33)
ICMP Host Unreachable from gateway sun (140.252.13.33)
^?                                     type interrupt key to stop
```

Test how far to know the host is not connected to the Internet: in this case about 6 routers


```
sun % ping 192.82.148.1
PING 192.82.148.1: 56 data bytes
ICMP Host Unreachable from gateway ensi142.UT.westnet.net (192.31.39.21)
for icmp from sun (140.252.1.29) to 192.82.148.1
```

this IP address is not connected to the Internet

To Forward or Not to Forward

- Hosts are not supposed to forward IP datagrams unless they have been specifically configured as a router:
 - Most Berkeley-derived implementations have a kernel variable named `ipforwarding`, or some similar name
 - Older 4.2 BSD hosts forwarded datagrams by default, which caused lots of problems for systems configured improperly. That's why this kernel option must always default to "never forward" unless the system administrator specifically enables forwarding

ICMP Redirect Errors



ICMP Redirect Errors

- An Example:

```
solaris % netstat -rn
Routing Table:
Destination      Gateway         Flags Ref    Use   Interface
-----
127.0.0.1        127.0.0.1      UH      0      848   lo0
140.252.1.0      140.252.1.32   U        3    15042  le0
224.0.0.0        140.252.1.32   U        3        0   le0
default          140.252.1.4    UG      0      5747  le0

solaris % ping -sv bsd1
PING bsd1: 56 data bytes
ICMP Host redirect from gateway gateway (140.252.1.4)
to netb (140.252.1.183) for bsd1 (140.252.1.35)
64 bytes from bsd1 (140.252.13.35): icmp_seq=0. time=383. ms
64 bytes from bsd1 (140.252.13.35): icmp_seq=1. time=364. ms
64 bytes from bsd1 (140.252.13.35): icmp_seq=2. time=353. ms
^C
type interrupt key to stop
----bsd1 PING Statistics----
4 packets transmitted, 3 packets received, 25% packet loss
round-trip (ms)  min/avg/max = 353/366/383
```

ICMP Redirect Errors


- (continued...)

```
solaris % netstat -rn
Routing Table:
Destination      Gateway         Flags Ref    Use   Interface
-----
127.0.0.1        127.0.0.1      UH      0      848   lo0
140.252.13.35    140.252.1.183  UGND    0        2
140.252.1.0      140.252.1.32   U        3    15045  le0
224.0.0.0        140.252.1.32   U        3        0   le0
default          140.252.1.4    UG      0      5749  le0
```

the route was installed by an ICMP redirect

ICMP Redirect Errors

- More Details:



the rules about ICMP redirects:

- generated only by routers, not by hosts
- intended to be used by hosts, not routers
- the routing protocol should obviate the need for redirects

code	Description
0	redirect for network
1	redirect for host
2	redirect for type-of-service and network
3	redirect for type-of-service and host


ICMP Router Discovery Messages

- Initialize a routing table by using newer ICMP router advertisement and solicitation messages:
 - bootstrapping ... broadcast/multicast solicitation message ... one or more routers responds with a router advertisement message
 - Additionally, the routers periodically broadcast/multicast their router advertisements, allowing any hosts that are listening to update their routing table accordingly
 - RFC 1256 specifies the format of these two ICMP messages:

ICMP Router Discovery Messages



- ♦ (continued...)



Wireless & Multimedia Network Laboratory™



ICMP Router Discovery Messages



- ♦ Router Operation:
 - When a router starts up it transmits periodic advertisements on all interfaces capable of broadcasting or multicasting
 - these advertisements are not exactly periodic, but are randomized
- ♦ Host Operations:
 - Upon bootstrap a host normally transmit three router solicitations, 3 seconds apart.
 - A host also listens for advertisements from adjacent routers.
- ♦ Implementation:
 - The router discovery message are normally generated by and processed by a user process (a daemon)

Wireless & Multimedia Network Laboratory™



Summary



- ♦ How a single IP layer makes its routing decisions
- ♦ Routing principles
- ♦ ICMP host and network unreachable errors
- ♦ ICMP redirect errors
- ♦ ICMP Router Discovery Messages

Wireless & Multimedia Network Laboratory™

